



danair

DANAIR

REFRIGERATION EQUIPMENT

GODANAIR.COM



Merchandising Swing Glass Door Refrigerator - NRJ Series

- Exterior: Coated steel. **Black or white finish available.**
- Interior: Attractive aluminum liner with stainless steel floor.
- Refrigeration system maintains temperatures between 33°F and 41°F (0.5°C to 5°C).
- Self-Closing double pane glass door with positive seal.
- Shelves: Adjustable heavy-duty PVC coated shelves.
- Refrigerant: **HYDRO-CARBON R290.**
- LED lighting.
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Leveling feet or casters are available.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- Very low energy consumption
- Black or white



GDC-2B-48-HC



GDC-2B-53-HC



GDC-3B-79-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
GDC-2B-48-HC	2	8	48 x 25 3/5 x 80 3/8	1220 x 650 x 2040	29 830	1/4+	4.8	115/60/1	NEMA 5-15P
GDC-2B-53-HC	2	8	53 1/8 x 31 7/8 x 79 3/8	1350 x 810 x 2015	45 1270	1/4+	4.3	115/60/1	NEMA 5-15P
GDC-3B-79-HC	3	12	78 3/8 x 30 x 80 3/4	1988 x 760 x 2050	53 1500	3/4	10.7	115/60/1	NEMA 5-20P

Specifications subject to change without notice.



Undercounter Freezer -TUCF Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between -8°F and 0°F (-22°C to -18°C).
- **Self-Closing doors** with 90 degree stay-open feature.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



TUC-27F-HC



TUC-48F-HC



TUC-60F-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY cu. ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
TUC-27F-HC	1	1	27 x 29 1/2 x 35 1/5	685 x 750 x 895	6.3 177	1/5	2.1	115/60/1	NEMA 5-15P
TUC-48F-HC	2	2	47 1/5 x 29 1/2 x 35 1/5	1200 x 750 x 895	12 338	1/4+	4.5	115/60/1	NEMA 5-15P
TUC-60F-HC	2	2	60 1/5 x 29 1/2 x 35 1/5	1526 x 750 x 895	15 428	1/2+	6.36	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Refrigerated Deli Case -PAT Series

- **Interior:** Aluminum liner with stainless steel floor.
- **Exterior:** Black or white coated steel. Stainless steel available.
- **Attractive curved glass and sliding glass doors.**
- **Rounded corner design** inside of the cabinet makes it easy to clean the inside storage room.
- **Refrigeration system** keeps the meats and deli products at safe temperatures between 32°F and 43°F (0°C to 6°C).
- **Refrigerant: HYDRO-CARBON R290.**
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **Preinstalled heavy-duty casters with brakes.**
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **LED interior lighting.**
- **Gravity coil,** ideal to keep your product perfect



PAT-48-HC



PAT-83-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY		HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm	cu.ft.	liters				
PAT-48-HC	2	6	47 1/4 x 32 1/2 x 42 7/8		18		1/4+	2.6	115/60/1	NEMA 5-15P
				1200 x 825 x 1089	508					
PAT-83-HC	3	9	82 x 32 1/2 x 42 7/8		32		3/4	5.9	115/60/1	NEMA 5-15P
				2082 x 825 x 1089	903					

Specifications subject to change without notice.



Dipping Cabinet - GC Series

- Stainless steel top with curved glass viewing window. Bright white painted steel interior and exterior.
- Refrigeration system keeps ice cream at temperatures between -10°F and 5°F (-23°C to -15°C).
- Transparent lids hinged with a full length handle.
- Plastic can holder for each container rack.
- LED lighting.
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- These units use HYDRO-CARBON R290 refrigerant, which is environmentally friendly and more efficient than R134a/R404a refrigerant.



CG-48-HC



CG-68-HC

MODEL	LIDS	RACKS	DIMENSIONS - WxDxH		CAPACITY(3gal. cans)		HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm	Display	Storage				
CG-48-HC	1	8	47 x 27 3/4 x 51 1/8		8		1/4+	5.16	115/60/1	NEMA 5-15P
				1195 x 705 x 1300	4					
CG-68-HC	2	12	67 3/4 x 27 3/4 x 51 1/8		12		1/2+	5.64	115/60/1	NEMA 5-15P
				1720 x 705 x 1300	8					

Specifications subject to change without notice.



Sandwich/Salad Prep Table -PRT Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors** with 90 degree stay-open feature.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Cutting boards and pans available.**
- **Options:** Over head shelves
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



PRT-1-28 HC



PRT-2-36 HC



PRT -2-47 HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
PRT-1-28 HC	1	1	27 1/2 x 29 1/2 x 42 3/8	698 x 750 x 1075	5.7 160	1/5	2.88	115/60/1	NEMA 5-15P
PRT-2-36 HC	2	2	36 1/4 x 29 1/2 x 42 3/8	920 x 750 x 1075	7.6 213	1/5	3.24	115/60/1	NEMA 5-15P
PRT -2-47 HC	2	2	46 7/8 x 29 1/2 x 42 3/8	1188 x 750 x 1075	9.5 268	1/4+	4.56	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Refrigerated Bakery Case with Curved Glass

- Exterior: Stainless steel exterior with 4-sided, double-glass
Front: Attractive curved glass
- Refrigeration system maintains temperatures between 36°F and 43°F (2°C to 6°C)
- Sliding glass door.
- Shelves: Adjustable heavy duty PVC coated shelves.
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- LED interior lighting.
- R290 natural refrigerant.



UCGBC-50-HC



UCGBC-59-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY		HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm	cu.ft.	liters				
UCGBC-50-HC	2	6	50 x 34 x 49 1/5	1270 x 865 x 1250	22.6	640	3/4	7.7	115/60/1	NEMA 5-15P
UCGBC-59-HC	2	6	59 x 34 x 49 1/5	1500 x 865 x 1250	27.2	770	3/4	8	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Back Bar Cooler - 24" Depth Glass Door Series

- Durable stainless steel top, interior walls, floor and ceiling.
- Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
- Refrigeration system keeps the drinks at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Preinstalled heavy-duty casters with brakes. Option of leveling feet available.
- Shelves: Adjustable heavy-duty PVC coated shelves.
- Self-Closing doors with locks.
- LED interior lighting.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- Refrigerant: HYDRO-CARBON R290.



UBB-49G-HC



UBB-61G-HC



UBB-73G-HC



UBB-91G-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
UBB-49G-HC	2	4	48 7/8 x 24 3/8 x 35 5/8	1240 x 620 x 905	11.8 335	1/5	2.88	115/60/1	NEMA 5-15P
UBB-61G-HC	2	4	60 3/4 x 24 3/8 x 35 5/8	1544 x 620 x 905	15.8 446	1/5	2.88	115/60/1	NEMA 5-15P
UBB-73G-HC	3	6	72 3/4 x 24 3/8 x 35 5/8	1848 x 620 x 905	19.6 556	1/4+	3.96	115/60/1	NEMA 5-15P
UBB-91G-HC	3	6	90 3/8 x 27 3/4 x 35 5/8	2295 x 705 x 905	32 916	1/4+	4.7	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Undercounter Refrigerator -TUCR Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors** with 90 degree stay-open feature.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Options:** Overhead shelves available
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



TUC-27R-HC



TUC-48R-HC
TUC-60R-HC



TUC-72R-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY cu. ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
TUC-27R-HC	1	1	27 x 29 1/2 x 35 1/5	685 x 750 x 895	6.3 177	1/6	1.9	115/60/1	NEMA 5-15P
TUC-48R-HC	2	2	47 1/5 x 29 1/2 x 35 1/5	1200 x 750 x 895	12 338	1/5	2.7	115/60/1	NEMA 5-15P
TUC-60R-HC	2	2	60 1/5 x 29 1/2 x 35 1/5	1526 x 750 x 895	15 428	1/5	2.9	115/60/1	NEMA 5-15P
TUC-72R-HC	3	3	72 x 29 1/2 x 35 1/5	1829 x 750 x 895	15.5 440	1/5	3.2	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Pizza Prep Table - PIZ Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors** with 90 degree stay-open feature.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Cutting boards and pans available.**
- **Options:** Overhead shelves available
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



PIZ-1-50 HC



PIZ-2-71 HC



PIZ-3-92 HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
PIZ-1-50 HC	1	1	49 7/8 x 31 1/2 x 42 7/8	1266 x 800 x 1088	13.8 391	1/6	2.64	115/60/1	NEMA 5-15P
PIZ-2-71 HC	2	2	70 9/10 x 31 1/2 x 42 7/8	1800 x 800 x 1088	16.9 477	1/5	3.42	115/60/1	NEMA 5-15P
PIZ-3-92 HC	3	3	91 9/10 x 31 1/2 x 42 7/8	2334 x 800 x 1088	24.2 684	1/4+	5.28	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Back Bar Cooler - 24" Depth Solid Door Series STAINLESS TOP

- Durable stainless steel top, interior walls, floor and ceiling.
- Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
- Refrigeration system keeps the drinks at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Preinstalled heavy-duty casters with brakes. Option of leveling feet available.
- Shelves: Adjustable heavy-duty PVC coated shelves.
- Self-Closing doors with locks.
- LED interior lighting.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- Refrigerant: HYDRO-CARBON R290.



UBB-49S-HC



UBB-61S-HC



UBB-73S-HC



UBB-91S-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
UBB-49S-HC	2	4	48 7/8 x 24 3/8 x 35 5/8	1240 x 620 x 905	11.8 335	1/5	2.88	115/60/1	NEMA 5-15P
UBB-61S-HC	2	4	60 3/4 x 24 3/8 x 35 5/8	1544 x 620 x 905	15.8 446	1/5	2.88	115/60/1	NEMA 5-15P
UBB-73S-HC	3	6	72 3/4 x 24 3/8 x 35 5/8	1848 x 620 x 905	19.6 556	1/4+	3.96	115/60/1	NEMA 5-15P
UBB-91S-HC	3	6	90 3/8 x 27 3/4 x 35 5/8	2295 X 705 X 905	32 916	1/4+	4.7	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Mega Top Sandwich/Salad Prep Table - PRTM Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors** with 90 degree stay-open feature.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Cutting boards and pans available.**
- **Options:** Glass top (Amir or Subway style)
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



PRTM-2-60 HC



PRTM-3-71 HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
PRTM-2-60 HC	2	2	60 1/5 x 34 x 45 9/10		15	1/4+	4.8	115/60/1	NEMA 5-15P
				1529 x 864 x 1166	428				
PRTM-3-71 HC	3	3	70 2/5 x 34 x 45 9/10		15.5	3/4	8.9	115/60/1	NEMA 5-15P
				1787 x 864 x 1166	440				

Specifications subject to change without notice.



Merchandising Sliding Glass Door Refrigerator - NRJ Series

- Exterior: Coated steel. **Black or white finish available.**
- Interior: Attractive aluminum liner with stainless steel floor.
- Refrigeration system maintains temperatures between 33°F and 41°F (0.5°C to 5°C).
- Self-Closing double pane glass door with positive seal.
- Shelves: Adjustable heavy-duty PVC coated shelves.
- Refrigerant: HYDRO-CARBON R290.
- Black or white
- LED lighting.
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Leveling feet or casters are available.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- Very low energy consumption
- Our best seller



GDC-2-53-HC black



GDC-2-53-HC white

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
GDC-2-53-HC	2	8	53 1/8 x 31 7/8 x 79 3/8		45	1/4+	4.3	115/60/1	NEMA 5-15P
				1350 x 810 x 2015	1270				

Specifications subject to change without notice.



Mega Top Sandwich/Salad Prep Table - PRTM Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors** with 90 degree stay-open feature.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Cutting boards and pans available.**
- **Options:** Overhead shelves or glasstop
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



PRTM-1-28 HC



PRTM-2-36 HC



PRTM-2-47 HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY cu. ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
PRTM-1-28 HC	1	1	27 1/2 x 34 x 45 9/10	698 x 864 x 1166	5.7 160	1/5	2.88	115/60/1	NEMA 5-15P
PRTM-2-36 HC	2	2	36 1/4 x 34 x 45 9/10	920 x 864 x 1166	7.6 213	1/5	3.24	115/60/1	NEMA 5-15P
PRTM-2-47 HC	2	2	46 7/8 x 34 x 45 9/10	1188 x 864 x 1166	9.5 268	1/4+	4.56	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Direct Draw Beer Dispenser - 27" Depth LIDB Series

- Durable stainless steel top, interior walls, floor and ceiling.
- Exterior construction is attractive corrosion resistant vinyl on steel in black finish.
- Refrigeration system keeps the drinks at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Preinstalled heavy-duty casters with brakes. Option of leveling feet available.
- Shelves: Adjustable heavy-duty PVC coated shelves.
- Self-Closing doors with locks.
- LED interior lighting.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- Refrigerant: HYDRO-CARBON R290.



UDB-1-24-HC



UDB-2-59-HC



UDB-2-70-HC



UDB-3-91-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY cu. ft. barrels	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
UDB-1-24-HC	1	2	23 1/2 x 30 3/8 x 38 3/4	596 x 772 x 983	6.5 1*1/2	1/6	1.92	115/60/1	NEMA 5-15P
UDB-2-59-HC	2	4	58 7/8 x 27 3/4 x 35 5/8	1495 x 705 x 905	19 2*1/2	1/5	2.88	115/60/1	NEMA 5-15P
UDB-2-70-HC	2	4	69 1/8 x 27 3/4 x 35 5/8	1755 x 705 x 905	23.3 3*1/2	1/5	3.6	115/60/1	NEMA 5-15P
UDB-3-91-HC	3	6	90 3/8 x 27 3/4 x 35 5/8	2295 x 705 x 905	32 4*1/2	1/4+	4.7	115//60/1	NEMA 5-15P

* Height does not include 15.8"(402mm) for draft arm.

Specifications subject to change without notice.



Cake Display Case - CD Series

- **Refrigeration system** maintains temperatures between 36°F and 43°F (2°C to 6°C).
- **Exterior:** Stainless steel floor and walls, standard. **Sliding doors.**
- 12V **LED lighting** system, safe for users to operate.
- **Tempered glass** to avoid injury by broken glass.
- Preinstalled hidden caster design.
- **Refrigerant: HYDRO-CARBON R290.**
- **Shelves:** Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation.
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **NSF-7** compliant for open food product.



CD-36-HC



CD-48-HC



CD-60-HC



CD-71-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
CD-36-HC	2	3	35 3/8 × 28 3/4 × 55 1/8	900 × 730 × 1400	12.7 360	1/3+	4	115/60/1	NEMA 5-15P
CD-48-HC	2	3	47 1/4 × 28 3/4 × 55 1/8	1200 × 730 × 1400	19.4 550	1/3+	8.05	115/60/1	NEMA 5-15P
CD-60-HC	2	3	59 1/8 × 28 3/4 × 55 1/8	1500 × 730 × 1400	25 700	1/2+	8.3	115/60/1	NEMA 5-15P
CD-71-HC	2	3	70 7/8 × 28 3/4 × 55 1/8	1800 × 730 × 1400	30 850	1/2+	9.2	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Reach-in Glass Door Refrigerator -SDC Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing glass doors with locks and keys.**
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- Option of different handles & control panels available.
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



SDC-1-29G- HC



SDC-2-54G- HC



SDC-3-81G- HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
SDC-1-29G- HC	1	3	29 x 32 1/4 x 82 1/2	736 x 818 x 2095	23 650	1/5	2.6	115/60/1	NEMA 5-15P
SDC-2-54G- HC	2	6	54 x 32 1/4 x 82 1/2	1371 x 818 x 2095	47 1321	1/4+	4.3	115/60/1	NEMA 5-15P
SDC-3-81G- HC	3	9	80 9/10 x 32 1/4 x 82 1/2	2054 x 818 x 2095	72 2040	3/4	9.1	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Merchandising Swing Glass Door Freezer - NRJ Series

- **Exterior:** Coated steel. **Black or white finish available.**
- **Interior:** Attractive aluminum liner with stainless steel floor.
- **Refrigeration system** maintains temperatures between -10°F and 0°F (-23°C to -18°C).
- **Self-Closing double pane glass door** with positive seal.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Refrigerant:** HYDRO-CARBON R290.
- **LED lighting.**
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Leveling feet or casters are available.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **Very low energy consumption**
- **Black or white**



GDF-1C-26-HC



GDF-1-27-HC



GDF-1-31-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
GDF-1C-26-HC	1	2	26 4/5 x 26 x 55 7/8	680 x 660 x 1420	8.5 240	1/4+	3.5	115/60/1	NEMA 5-15P
GDF-1-27-HC	1	4	27 1/5 x 26 1/5 x 80 3/8	690 x 665 x 2040	13 368	3/4	8.8	115/60/1	NEMA 5-15P
GDF-1-31-HC	1	4	31 1/8 x 31 3/8 x 80 3/4	790 x 795 x 2050	23 648	3/4	9.4	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Intertek Intertek

Merchandising Swing Glass Door Refrigerator - NRJ Series

- **Exterior:** Coated steel. **Black or white finish available.**
- **Interior:** Attractive aluminum liner with stainless steel floor.
- **Refrigeration system** maintains temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing double pane glass door** with positive seal.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Refrigerant:** HYDRO-CARBON R290.
- **LED lighting.**
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Leveling feet or casters are available.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **Very low energy consumption**



GDC-1-22-HC



GDC-1-26-HC



GDC-1-29-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
GDC-1-22-HC	1	4	21 5/8 x 21 5/8 x 63	550 x 550 x 1600	9.1 258	1/5	2.88	115/60/1	NEMA 5-15P
GDC-1-26-HC	1	4	26 x 25 3/5 x 80 3/8	660 x 650 x 2040	14 368	1/5	2.88	115/60/1	NEMA 5-15P
GDC-1-29-HC	1	4	28 3/8 x 31 7/8 x 79 3/8	720 x 810 x 2015	23 648	1/5	3	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Reach-in Solid Door Refrigerator - SDC Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors** with 90 degree stay-open feature. Locks and keys included.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Options:** Baking rack
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



SDC-1-29 HC



SDC-2-54 HC



SDC-3-81 HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY cu. ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
SDC-1-29 HC	1	3	29 x 32 1/4 x 82 1/2	736 x 818 x 2095	23 650	1/5	2.6	115/60/1	NEMA 5-15P
SDC-2-54 HC	2	6	54 x 32 1/4 x 82 1/2	1371 x 818 x 2095	47 1321	1/4+	3.8	115/60/1	NEMA 5-15P
SDC-3-81 HC	3	9	80 9/10 x 32 1/4 x 82 1/2	2054 x 818 x 2095	72 2040	3/4	9	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Merchandising Swing Glass Door Freezer - NRJ Series

- Exterior: Coated steel. **Black or white finish available.**
- Interior: Attractive aluminum liner with stainless steel floor.
- Refrigeration system maintains temperatures between -10°F and 0°F (-23°C to -18°C).
- Self-Closing double pane glass door with positive seal.
- Shelves: Adjustable heavy-duty PVC coated shelves.
- Refrigerant: HYDRO-CARBON R290.
- LED lighting.
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Leveling feet or casters are available.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- Very low energy consumption



GDF-2-48-HC



GDF-2-53-HC



GDF-3-79-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
GDF-2-48-HC	2	8	49 1/5 x 26 1/5 x 80 3/8	1250 x 665 x 2040	29 830	3/4	9.4	115/60/1	NEMA 5-20P
GDF-2-53-HC	2	8	53 1/8 x 31 7/8 x 79 3/8	1350 x 810 x 2015	45 1270	1	9.2	115/60/1	NEMA 5-20P
GDF-3-79-HC	3	12	79 1/2 x 30 3/5 x 80 3/4	2020 x 777 x 2050	52 1479	0.75 x 2	16.3	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Chef Base Refrigerator - BR Series

- **Stainless steel interior and exterior** retains attractive finish longer. Matching aluminum finished back.
- **Stainless steel top equipped with a marine edge** enables the unit's top to contain drips and spills for easy cleanup.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Preinstalled heavy-duty casters with brakes.**
- **Heavy-duty pull handles.**
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



BR-36 HC



BR-52 HC



BR-72 HC

MODEL	DRAWERS	GN PANS	DIMENSIONS - WxDxH		CAPACITY	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
BR-36 HC	2	2*1/1+6*1/6	36 3/8 x 32 1/8 x 25 3/8	924 x 816 x 645	5.9 167	1/6	2.52	115/60/1	NEMA 5-15P
BR-52 HC	2	6*1/1	51 7/8 x 32 1/8 x 25 3/8	1318 x 816 x 645	9.9 280	1/6	3.48	115/60/1	NEMA 5-15P
BR-72 HC	4	8*1/1	72 3/8 x 32 1/8 x 25 3/8	1839 x 816 x 645	15 425	1/5	4.68	115/60/1	NEMA 5-15P

Specifications subject to change without notice.



Reach-in Solid Door Freezer - SDF Series

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between -8°F and 0°F (-22°C to -18°C).
- **Self-Closing doors** with 90 degree stay-open feature. Locks and keys included.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Options:** Baking rack
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



SDF-1-29 HC



SDF-2-54 HC



SDF-3-81 HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY cu.ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
SDF-1-29 HC	1	3	29 x 32 1/4 x 82 1/2	736 x 818 x 2095	23 650	1/2+	7.1	115/60/1	NEMA 5-15P
SDF-2-54 HC	2	6	54 x 32 1/4 x 82 1/2	1371 x 818 x 2095	47 1321	1	10.7	115/60/1	NEMA 5-20P
SDF-3-81 HC	3	9	80 9/10 x 32 1/4 x 82 1/2	2054 x 818 x 2095	72 2040	1 1/4	12	115/60/1	NEMA 5-20P

Specifications subject to change without notice.



Sandwich/Salad Prep Table -PRTSeries

- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors** with 90 degree stay-open feature.
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Cutting boards and pans available.**
- **Options:** Overhead shelves
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.



PRT-2-60 HC



PRT-3-71 HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH		CAPACITY cu. ft. liters	HP	AMPS	VOLTAGE	PLUG TYPE
			inches	mm					
PRT-2-60 HC	2	2	60 1/5 x 29 1/2 x 42 3/8		15	1/4+	4.8	115/60/1	NEMA 5-15P
				1529 x 750 x 1075	428				
PRT-3-71 HC	3	3	70 2/5 x 29 1/2 x 42 3/8		15.5	3/4	8.9	115/60/1	NEMA 5-15P
				1787 x 750 x 1075	440				

Specifications subject to change without notice.

